

CSL901

Equipment Cleaner

Technical Data Sheet

Electrical & Electronic



TYPICAL USES

- Ideal for equipment cleaning
- Ideal for spray line flushing

PRODUCT DESCRIPTION

CSL901 equipment cleaner is a narrow range, low end-point mineral spirits. It has the typical high flash point of a Stoddard solvent, but it evaporates in approximately half the time. CSL901 is used where a slightly faster evaporation rate is required while maintaining the flash point above 30°C. It is the same solvent used in the Coating, and is compatible for cleaning equipment and spray lines.

PHYSICAL PROPERTIES

(Typical properties - values not to be used as specifications)

Appearance	Clear liquid
Specific Gravity	0.78
Flash Point C (Tag Closed Cup)	38°C

COLORS

CSL901 is Clear.

SAFETY PRECAUTIONS

CSL901 Equipment Cleaner is flammable. Keep away from open flames and heat. Use with adequate ventilation and avoid prolonged breathing of vapors. Before handling, read product Safety Data Sheet (SDS).

PACKAGING

CSL901 is supplied in 3.8 L (1 gallon) cans, and 19 L (5 gallons) pails.

STORAGE

CSL901, when stored in original, unopened container in dry, shaded conditions, away from sources of heat or ignition, and stored at or below 32°C (90°F), has a shelf life of 12 months from date of manufacture.

WARRANTY

CSL Silicones Inc. warrants that its products will meet its specifications. CSL shall in no event be liable for incidental or consequential damages. Except as expressly stipulated, CSL's liability, expressed or implied, is limited to the stated selling price of any defective goods.

Data is subject to change without notice and it is therefore recommended that this information not be used for specification writing. For additional information on specific applications, contact the manufacturer.

CSL is ISO 9001:2008 Registered

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this document without first obtaining written confirmation from CSL Silicones Inc. as to the suitability of the product for the intended purpose does so at his/her own risk. The information contained herein has been prepared in good faith to comply with applicable federal and provincial (state) law(s). However, no warranty of any kind is given or implied and CSL Silicones Inc. will not be responsible for any damages, losses or injuries that may result from the use of any information contained herein. While CSL endeavors to ensure all advice it gives about the product (whether in this document or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless CSL specifically agrees in writing to do so, it does not accept any liability whatsoever or howsoever arising for the performance of the product, or for any consequential loss or damage arising out of the use of the product. Any warranty, if given or specific Terms & Conditions of Sale are contained in CSL's Terms & Conditions of Sale, a copy of which can be obtained upon request. The information contained herein is liable to modification from time-to-time in light of experience and CSL's policy of continuous product improvement. It is the user's responsibility to check that this document is current prior to using the product. This document must not be used for specification writing.

CSL Silicones Inc.
144 Woodlawn Rd. W.
Guelph, ON N1H 1B5
Canada

T +1 519.836.9044
F + 1 519.836.9069
TF + 1 800.265.2753

www.cslsilicones.com

CSL901 Reviewed 2016-03-09

All trademarks registered. All rights reserved