



# Transgel

For the removal of older, hardened and sunbaked spray can and acrylic paints from masonry, metal, asphalt and timber surfaces

## Product Data Sheet

Product Code: WB0050

Issued: August 8, 2016

### PRODUCT DESCRIPTION

Highly effective, safe and BIODEGRADABLE paint remover for older, hardened and sun baked spray cans from masonry, metal, asphalt and timber surfaces.

Recommended for the removal of graffiti from road surfaces, including asphalt, tarmac, or bitumen without degradation of the road surface. Can be used on unpainted metals and pre-painted steel fencing.

TRANSGEL will remove hard sun-baked murals on trains left in yards and thicker spray can and acrylic murals from buildings. TRANSGEL is particularly useful for removing old and hardened white and yellow spray cans.

### FEATURES & BENEFITS

- Fast acting and non-damaging.
- Works on all building surfaces, from porous cinderblock to smooth paintwork, powdercoat and asphalt.
- Virtually odorless and non toxic.
- Gel consistency, stays wetter longer ensuring maximum dwell time in order to crinkle thicker / older paint.



Leave TRANSGEL on for extended periods in order to crinkle up multi-layered paint before rinsing with a pressure washer.

### INSTRUCTIONS FOR USE

#### For typical removal jobs on graffiti and other paint

Apply thickly, and leave for at least 20 minutes dwell time. Longer dwell times may be necessary in some circumstances. Agitate with a stiff nylon brush or scrub pad if the graffiti is very thick. Rinse with high pressure water. Best results are obtained using a hot water pressure washer.

**FOR EXPERT TECHNICAL ADVICE ON YOUR REMOVAL JOB,  
PLEASE CALL 1-818-247-2555 OR  
EMAIL SALES@GRAFFITIREMOVALINC.COM**



When removing older, multilayered graffiti and acrylic paint, TRANSGEL can be left to work overnight as it will generally not dry out. This should only be done where it is safe to do so.

Once the thick layers of graffiti have been removed from porous surfaces using TRANSGEL, the remaining graffiti residue can be removed using BARE BRICK, STONE & MASONRY REMOVER.



Ideal for removing spray can from asphalt / bitumen without damage.

### TIPS FOR EFFECTIVE USE OF TRANSGEL

**TIP 1:** When rinsing TRANSGEL from wall, the use of a HOT WATER pressure washer will enhance results dramatically especially when removing thicker acrylic paints.

**TIP 2:** Transgel can be applied by airless sprayer on larger removal jobs such as murals and train cars.

**TIP 3:** For some thicker spray cans you can apply our BARE BRICK STONE & MASONRY REMOVER first, and then apply a coat of TRANSGEL over the top. This can be especially useful to enhance results in colder climates.



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



# Transgel

For the removal of older, hardened and sunbaked spray can and acrylic paints from masonry, metal, asphalt and timber surfaces

## Product Data Sheet

Product Code: WB0050

Issued: August 8, 2016

### SAFETY ISSUES

TRANSGEL is very safe to use in comparison with many other paint removal products and does not give off any fumes. Wear gloves and protective glasses to avoid eye and skin contact.



### LIMITATIONS

TRANSGEL is a highly effective and 'green' paint stripper for thicker / older spray can paints, and even acrylic and latex paint.

As with all paint removal jobs 'dwell time' is the most important factor. A pressure washer is always the last thing started. TRANSGEL is not designed to remove all types of coatings, so testing in the initial stages is always advisable.

### CAUTION

Before commencing any large scale use, always test first in an inconspicuous area. This product is designed to remove all types of markers and stains, and may have an unpredictable or even damaging result on certain man-made or stained surfaces. If necessary wait for surface to dry to ensure perfect results.

### COVERAGE GUIDELINES

Varies dependent upon the porosity of the surface, material and the type of paint being removed.

Coverage Guidelines are:

- 150 sq ft per gallon (per three coats on typical graffiti) for concrete
- 80 – 100sq ft per gallon on sandstone, limestone or other soft absorbent surfaces, or on thicker paints where additional coats are required.



Mural removal after spraying TRANSGEL with airless paint sprayer.

### TEMPERATURE USAGE

Used in all temperatures up to 100°F / 38°C and as low as 20°F / -6° C. Expect considerably slower reaction times in weather below 40° F / 5°C.

### TECHNICAL DATA

#### Composition

TRANSGEL is an ultra safe, thickened paint removal gel made from natural alcohols, and surfactants, designed to crinkle up and dissolve all kinds of paints and rinse away easily.

#### Properties

Color: Clear to yellowish liquid

Odor: Gentle alcohol odor.

PH: ~ 9

Storage: Store in a cold dry place away from heat or flames.

Shelf Life: Approximately 2 years but up to 5 years in unopened container.

Precautions: Harmful if swallowed or if inhaled. Causes skin irritation. Use protective clothing, eye protection and gloves.



TRANSGEL is used for removing old, thicker, baked on graffiti from trains.



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



# Transgel

For the removal of older, hardened and sunbaked spray can and acrylic paints from masonry, metal, asphalt and timber surfaces

## Product Data Sheet

Product Code: **WB0050**

Issued: **August 8, 2016**

### ENVIRONMENTAL CARE

TRANSGEL is biodegradable and conforms to all statutory environmental requirements for graffiti removal including VOC limits. Designed to be fast, effective and non-damaging. If necessary, water can be collected using a wet vac and disposed of safely.

We believe nothing other than rainwater should enter our precious storm water systems.

See SDS for further information.

### LEGAL DISCLAIMER

Read and follow label directions and observe all safety precautions in the use of this product. Because conditions of product use are outside of our control and vary widely, the following is made in lieu of all express or implied warranties: This product will conform to Urban Restoration Group US, Inc.'s published product specifications and be free from defects in material and manufacture on the date of purchase.

Except where prohibited by law, Urban Restoration Group US Inc., further disclaims, and shall not be liable for any incidental, special, consequential or indirect loss or damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced, regardless of the legal theory asserted.

**SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS PRODUCT AND MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, URBAN RESTORATION GROUP US, INC'S LIABILITY SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF THE PRODUCT PURCHASED.**

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of Urban Restoration Group US, Inc. products.

This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. Urban Restoration Group US, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

If this product is defective upon your receipt, your exclusive remedy shall be, at Urban Restoration Group US, Inc.'s option, to replace the product or refund the purchase price of the Urban Restoration Group US, Inc. product.

### CONTACT MANUFACTURER

Urban Restoration Group US Inc.  
5439 San Fernando Rd. W., Los Angeles CA 90039 USA  
Tel: +1-818-247-2555. Fax: +1-818-247-2515  
Email: [sales@graffitiremovalinc.com](mailto:sales@graffitiremovalinc.com)  
Web: [www.graffitiremovalinc.com](http://www.graffitiremovalinc.com)



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: [sales@graffitiremovalinc.com](mailto:sales@graffitiremovalinc.com). WEB: [www.graffitiremovalinc.com](http://www.graffitiremovalinc.com)