



Powerful and consistent cyclone head delivers efficient, even cleaning.



Built in headlight for night time use.



Excellent maneuverability for corners, curbs and other hard to reach areas.



Single-pass cleaning to remove ground in dirt, heavy build up and surface stains efficiently, without damage to the surface.



Hard Surface
Deep Cleaning
with Built-in
Recovery and
Maneuverability

KEY FEATURES AND BENEFITS

- Instantaneous water recovery
- Chemical free – allows deep impact cleaning with the use of only water and heat
- Aids in EPA compliance with environmentally friendly technology
- Multi-patented Cyclone head provides easy one-pass cleaning for increased efficiency
- Greatly increased productivity and the ability to drastically reduce the amount of time needed to clean large spaces
- Can be used with any current pressure washing system as well as other Cyclone products

HOW IT WORKS

- A vortex of air and water equivalent to a category 4 cyclone storm is created and controlled from the operator's seat, allowing maximum results on a variety of surfaces – concrete, asphalt, cobblestone, athletic running tracks and more
- The cleaning head features 2 high-pressure water nozzles and 8 turbine blades that rotate at high speed. The continuous air movement creates lift that recovers water while removing dirt and debris
- The swirling vortex of air and waste water further scours the surface – resulting in an exceptionally deep clean in a single pass
- Waste water is flung by the air movement into a holding tank, where it is then pumped into the water reclaim tank – completing the waste water recovery process without a vacuum system
- Cyclone Technology's non-vacuum design means less maintenance and lower annual fuel cost; resulting in a faster return on investment

Faster, Greener, Cleaner



The Cyclone Difference

CYCLONE CY210 TECHNICAL SPECIFICATIONS

Model	Cyclone CY210
Cleaning Path	18in. (.46m)
Input Pressure	Up to 5500psi (379.2bar)
Pump Recommendations	Minimum pump recommendations: 2,000psi at 4GPM (137.9bar at 15.1LPM)
Input Temperature	Up to 200°F (93°C)
Power Source	Honda gasoline with electric start
Pressure Connections	Supply: 3/8in. (.0095M) male quick connect / Recovery: 1in. (.025m) cam lock
Spray Tips	2 spray tips protected by vented plate
Battery	12V for starting
Weight	410lb. (185kg)
Dimensions (L x W x H)	68in. (1.72m) x 35in. (.89m) x 42in. (1.06m)

Specifications are subject to change without notice.



CY210-SHOWN WITH THE TR5500



CY210-SHOWN WITH THE CY5000

Contact Us For More Information

1-800-335-9695

info@cycloneclean.com

www.cycloneclean.com

 [Facebook.com/cycloneclean](https://www.facebook.com/cycloneclean)

 [Twitter.com/cyclonetech](https://twitter.com/cyclonetech)



For Europe, Middle East & Africa Sales:
Dieter Pade, Vice President Int. Sales
Cell: +43 (664) 1256902
Email: office@dpade.com